



FRP

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock® FRP Spray Adhesive bonds approved wall material for commercial and residential applications. Material must be structurally sound for use in commercial or residential applications.

Spray-Lock® FRP Spray Adhesive uses 60% less adhesive than traditional trowel-on adhesives.

Spray-Lock® FRP Spray Adhesive increases productivity with a faster application rate, saving time and money. Spray-Lock® FRP Spray Adhesive comes in easy-to-use aerosol .

ADVANTAGES

- Cuts labor cost by about 30%
- 4 hour working time
- Apply directly to wall / Instant grab
- Releasable for repositioning (prior to rolling)
- Adheres to porous and non-porous substrates
- 0.020 g/ml VOC content
- Non-toxic, water-based adhesive
- Easy water cleanup while adhesive is still wet
- Non-flammable
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® FRP Spray Adhesive adheres approved wall coverings onto the following properly prepared smooth substrates:

- Drywall
- FRP
- Metal
- DensShield
- Ceramic Tile

NOTE: Joint compound may need to be primed if it continues to dust.

TECHNICAL CHARACTERISTICS

Spray-Lock® FRP Spray Adhesive formula is a water-based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock® FRP Spray Adhesive is solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock® FRP Spray Adhesive uses non-ozone depleting HFC propellant.

*Green Seal Certified: This product meets Green Seal™ Standard GS-36 based on effective performance and protective limits on VOCs and human and environmental toxicity. GreenSeal.org.

**According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	4 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
STORAGE	Do not subject to freezing temperatures



COVERAGE GUIDE

FRP ADHESIVE | 22 oz AEROSOL CAN

70 sq ft (6.5 m²)
2 sheets (8ft x 4ft)

Shake aerosol can well. Snap blue tab on top of trigger to activate the can. Aim at desired substrate. Pull blue lever to spray adhesive.

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented. Please refer to Installation Guidelines for detailed instructions.