

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Date of issue: 11/13/2014 Revision date: 05/15/2015 Version: 1.0

SECTION 1: Identification of the su	ibstance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: RugLock
Product code	: Not available.
1.2. Relevant identified uses of the sul	bstance or mixture and uses advised against
Use of the substance/mixture	: Adhesive.
1.3. Details of the supplier of the safet	y data sheet
Spray-Lock, Inc. 5959 Shallowford Road, Suite 405 Chattanooga, TN 37421 - USA T 423-305-6151	
1.4. Emergency telephone number	
Emergency number	: CHEMTREC: 1 (800) 424-9300
SECTION 2: Hazards identification	
2.1. Classification of the substance or	mixture
GHS-US classification	
Gases Under Pressure - Dissolved gas	
Gases Onder Pressure - Dissorved gas	
2.2. Label elements	
GHS-US labelling	
Hazard pictograms (GHS-US)	: GHS04
Signal word (GHS-US)	: Warning
Hazard statements (GHS-US)	: Contains gas under pressure; may explode if heated.
Precautionary statements (GHS-US)	: Protect from sunlight. Store in a well-ventilated place.
2.3. Other hazards	
No additional information available.	
2.4. Unknown acute toxicity (GHS-US)	
None	
SECTION 3: Composition/informati	ion on ingredients
3.1 Substance	

3.1. Substance

Not applicable.

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	30 - 60	Not classified.
Quartz	(CAS No) 14808-60-7	0.1 - 1	Acute Tox. 4 (Oral) Carc 1A ¹ STOT RE 1 ¹
1,4-Dioxane	(CAS No) 123-91-1	< 0.1	Flam. Liq. 2 Eye Irrit. 2A Carc. 2 STOT SE 3

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Ethylene oxide	(CAS No) 75-21-8	< 0.1	Flam. Gas 1 Press. Gas Acute Tox. 3 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1B STOT SE 3

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

¹ Only applies to airborne particles of respirable size.

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.	
First-aid measures after skin contact	In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.	
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.	
First-aid measures after ingestion	: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.	
4.2. Most important symptoms and effec	ts, both acute and delayed	
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.	
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.	
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
Symptoms/injuries after ingestion	: Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.	
4.3. Indication of any immediate medical	attention and special treatment needed	
Symptoms may not appear immediately. In case of	accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).	
SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Water spray, dry chemical, foam, carbon dioxide.	
Unsuitable extinguishing media	None known.	
5.2. Special hazards arising from the sub	ostance or mixture	
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.	
	· · · · · · · · · · · · · · · · · · ·	
5.3. Advice for firefighters Protection during firefighting	: Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.	
SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equ		
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.	
6.2. Methods and material for containme	nt and cleaning up	
For containment	: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).	
Methods for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.	
6.3. Reference to other sections		
See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.		
SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	: Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Do not swallow. When using do not eat, drink or smoke. Pressurized container: Do not pierce or burn, even after use. Use only in well-ventilated areas.	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures

: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Keep out of the reach of children. Store away from direct sunlight or other heat sources. Do not store at temperatures above 49 °C / 120 °F. Keep from freezing. Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Limestone (1317-65-3)			
USA ACGIH	ACGIH TWA (mg/m³)	10 mg/m³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total) 5 mg/m³ (resp)	
Quartz (14808-60-7)			
USA ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	((10 mg/m³)/(%SiO ₂ +2) TWA (resp)) ((30 mg/m³)/(%SiO ₂ +2) TWA (total)) ((250)/(%SiO ₂ +5) mppcf TWA (resp))	
1,4-Dioxane (123-91-1)			
USA ACGIH	ACGIH TWA (ppm)	20 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
Ethylene oxide (75-21-8)			
USA ACGIH	ACGIH TWA (ppm)	1 ppm	
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm	

Exposure controls 8.2.

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

9.1. Information on basic physical and	d chemical properties
Physical state	: Gas/Pressurized Liquid.
Appearance	: Opaque.
Color	: White.
Odor	: Odorless.
Odor threshold	: No data available.
рН	: 6 - 8
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
05/15/2015	EN (English)

SECTION 9: Physical and chemical properties

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: No data available.
Relative vapor density at 20 °C	: > 1 (Air = 1)
Relative density	: > 1.1
Solubility	: Miscible.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available.

SECT	ION 10: Stability and reactivity			
10.1.	Reactivity			
No dang	gerous reaction known under conditions of normal use.			
10.2.	Chemical stability			
Stable ι	under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.			
10.3.	Possibility of hazardous reactions			
No dang	No dangerous reaction known under conditions of normal use.			
10.4.	Conditions to avoid			
Heat. In	acompatible materials. Sources of ignition.			
10.5.	Incompatible materials			

Oxidizers. Nitrates. Chlorine bleach.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Not classified.

RugLock		
LD50 oral rat	> 2000 mg/kg	
LD50 dermal rabbit	No data available.	
LC50 inhalation rat	No data available.	
Limestone (1317-65-3)		
LD50 oral rat	6450 mg/kg	
Quartz (14808-60-7)		
LD50 oral rat	500 mg/kg	
1,4-Dioxane (123-91-1)		
LD50 oral rat	7600 mg/kg	
LD50 dermal rabbit	4200 mg/kg	
LC50 inhalation rat	48.5 mg/l/4h	
Ethylene oxide (75-21-8)		
LD50 oral rat	72 mg/kg	
LC50 inhalation rat	800 ppm/4h	
Skin corrosion/irritation	: Based on available data, the classification criteria are not met.	
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.	
Respiratory or skin sensitization	: Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.	
Carcinogenicity	: Based on available data, the classification criteria are not met.	

RugLock Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)		
IARC group	1 - Carcinogenic to humans (Only applies to airborne particles of respirable size)	
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens (Only applies to airborne particles of respirable size)	
1,4-Dioxane (123-91-1)		
IARC group	2B - Possibly carcinogenic to humans	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen	
Ethylene oxide (75-21-8)		
IARC group	1 - Carcinogenic to humans	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens	
	In OSHA Specifically Regulated Carcinogen list	
Reproductive toxicity	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.	
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.	
Aspiration hazard	: Based on available data, the classification criteria are not met.	
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.	
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin	
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.	
Symptoms/injuries after ingestion	: Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.	

SECTION 12: Ecological information			
12.1. Toxicity			
Ecology - general	: May cause long-term adverse effects in the aquatic environment.		
12.2. Persistence and degradability			
RugLock			
Persistence and degradability	Not established.		
12.3. Bioaccumulative potential			
RugLock			
Bioaccumulative potential	Not established.		
12.4. Mobility in soil			
No additional information available.			
12.5. Other adverse effects			
Effect on ozone layer	: No additional information available.		
Effect on the global warming	: No known ecological damage caused by this product.		
SECTION 13: Disposal considerations			
13.1. Waste treatment methods			

: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

SECTI	ON 14: Transport information		
In accordance with DOT			
14.1.	UN number		
UN-No.(DOT)		UN1950	
14.2.	UN proper shipping name		
Proper Shipping Name (DOT)		: Aerosols	
Department of Transportation (DOT) Hazard Classes		: 2.2	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

1

Hazard labels (DOT)



14.3. Additional information

Other information

: No supplementary information available.

Special transport precautions

: Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

1,4-Dioxane (123-91-1)				
isted on United States SARA Section 313				
SARA Section 313 - Emission Reporting	0.1 %			
Ethylene oxide (75-21-8)				
Listed on the United States SARA Section 302 Listed on United States SARA Section 313				
SARA Section 302 Threshold Planning Quantity (TPQ)	1000			
SARA Section 313 - Emission Reporting	0.1 %			

Pugl ook

RugLock						
State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth					
	defects or other reproductive harm.					

SECTION 16: Other information	
Indication of changes	: None.
Date of issue	: 11/13/2014
Other information	: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

31-SDS-SL-RUGLOCK DATE: 05/15/2015 REV: A