

FOR EXCLUSIVE USE IN WALMART CONSTRUCTIONS

PLATINUM

High Moisture Adhesive

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

LVT22P6UD is a self-contained spray system that is engineered to adhere luxury vinyl tile and plank to concrete, underlayment grade plywood, metal, and fiberglass substrates.

LVT22P6UD is warranted to withstand concrete moisture emissions up to 10 lbs/24 hrs/1000 ft² or 98% RH and pH up to 12.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.020 g/ml VOC content
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

SUITABLE SUBSTRATES

LVT22P6UD bonds approved Luxury Vinyl Plank to the following properly prepared, smooth, flat, dust-free substrates:

- Concrete

TECHNICAL CHARACTERISTICS

LVT22P6UD provides immediate shear strength after installation, allowing instant access to finished floor.

LVT22P6UD is solvent-free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

LVT22P6UD uses non-ozone depleting HFC propellant.

LVT22P6UD withstands 10 lbs of vapor emissions, 98% RH and 12 pH.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



www.spraylock.com
423.305.6151

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	2 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 10 lbs/1000 sq ft or 98% RH/12 pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



COVERAGE GUIDE

LVT FLOORING | UPSIDE DOWN AEROSOL
125 sq ft

STANDARD APPLICATION

Shake aerosol can well. Remove white cap. Stand straight up to spray. Hold can upside down, approximately 20-30 inches (50-76 cm) horizontally from the substrate, aim at floor and press tip with finger.

LEVER APPLICATION

Slide lever prongs underneath valve collar, point tip towards substrate. Press lever to spray adhesive. This is perfect for all sized jobs. Cutting in is simple and most importantly it keeps the installer standing upright.