

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name : Ruglock  
Product code : Not available.

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive.

### 1.3. Details of the supplier of the safety data sheet

Interlock Industries, Inc.  
5959 Shallowford Road Suite 509  
Chattanooga, TN 37421 - USA  
T 423-305-6151

### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1 (800) 424-9300

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Gases Under Pressure - Liquefied gas

### 2.2. Label elements

#### GHS-US labelling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) : Warning  
Hazard statements (GHS-US) : Contains gas under pressure; may explode if heated.  
Precautionary statements (GHS-US) : Protect from sunlight. Store in a well-ventilated place.

### 2.3. Other hazards

No additional information available.

### 2.4. Unknown acute toxicity (GHS-US)

15 percent of the mixture consists of ingredient(s) of unknown acute toxicity.

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable.

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Limestone	(CAS No) 1317-65-3	30 - 60	Not classified.
Quartz	(CAS No) 14808-60-7	0.1 - 1	Acute Tox. 4 (Oral) Carc 1A <sup>1</sup> STOT RE 1 <sup>1</sup>
1,4-Dioxane	(CAS No) 123-91-1	< 0.1	Flam. Liq. 2 Eye Irrit. 2A Carc. 2 STOT SE 3

# Ruglock

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Ethylene oxide	(CAS No) 75-21-8	< 0.1	Flam. Gas 1 Press. Gas Acute Tox. 3 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A Muta. 1B Carc. 1B STOT SE 3

\* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

<sup>1</sup> Only applies to airborne particles of respirable size.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray, dry chemical, foam, carbon dioxide.
- Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

#### 5.3. Advice for firefighters

- Protection during firefighting : Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Use water spray to keep fire-exposed containers cool.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

#### 6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

#### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Do not swallow. When using do not eat, drink or smoke. Pressurized container: Do not pierce or burn, even after use. Use only in well-ventilated areas.

# Ruglock

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Store away from direct sunlight or other heat sources. Do not store at temperatures above 49 °C / 120 °F. Keep from freezing. Store in a well-ventilated place.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Limestone (1317-65-3)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total) 5 mg/m <sup>3</sup> (resp)
Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)) ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)) ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))
1,4-Dioxane (123-91-1)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Ethylene oxide (75-21-8)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	1 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear suitable gloves.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas/Pressurized Liquid.

Appearance : Opaque.

Color : White.

Odor : Odorless.

Odor threshold : No data available.

pH : 6 - 8

Relative evaporation rate (butylacetate=1) : No data available.

Melting point : No data available.

Freezing point : No data available.

Boiling point : No data available.

Flash point : No data available.

Auto-ignition temperature : No data available.

Decomposition temperature : No data available.

Flammability (solid, gas) : Not flammable.

# Ruglock

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapor pressure	: No data available.
Relative vapor density at 20 °C	: > 1 (Air = 1)
Relative density	: > 1.1
Solubility	: Miscible.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

### 9.2. Other information

No additional information available.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2. Chemical stability

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

### 10.5. Incompatible materials

Oxidizers. Nitrates. Chlorine bleach.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified.

Ruglock	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	No data available.
LC50 inhalation rat	No data available.
Limestone (1317-65-3)	
LD50 oral rat	6450 mg/kg
Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg
1,4-Dioxane (123-91-1)	
LD50 oral rat	7600 mg/kg
LD50 dermal rabbit	4200 mg/kg
LC50 inhalation rat	48.5 mg/l/4h
Ethylene oxide (75-21-8)	
LD50 oral rat	72 mg/kg
LC50 inhalation rat	800 ppm/4h

Skin corrosion/irritation	: Based on available data, the classification criteria are not met.
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.
Respiratory or skin sensitization	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.

# Ruglock

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans (Only applies to airborne particles of respirable size)
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens (Only applies to airborne particles of respirable size)
<b>1,4-Dioxane (123-91-1)</b>	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 3 - Reasonably anticipated to be Human Carcinogen
<b>Ethylene oxide (75-21-8)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity, 2 - Known Human Carcinogens
	In OSHA Specifically Regulated Carcinogen list

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: Not a normal route of exposure. May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

#### 12.2. Persistence and degradability

##### Ruglock

Persistence and degradability : Not established.

#### 12.3. Bioaccumulative potential

##### Ruglock

Bioaccumulative potential : Not established.

#### 12.4. Mobility in soil

No additional information available.

#### 12.5. Other adverse effects

Effect on ozone layer : No additional information available.

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

UN-No.(DOT) : UN1950

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Aerosols

Department of Transportation (DOT) Hazard Classes : 2.2

# Ruglock

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) :



### 14.3. Additional information

Other information : No supplementary information available.  
Special transport precautions : Do not handle until all safety precautions have been read and understood.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Propanol, 2-(methylamino)-2-methyl-	CAS No 27646-80-6
-------------------------------------	-------------------

#### 1,4-Dioxane (123-91-1)

Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

#### Ethylene oxide (75-21-8)

Listed on the United States SARA Section 302

Listed on United States SARA Section 313

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
--	------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

### 15.3. US State regulations

#### Ruglock

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	---

## SECTION 16: Other information

Indication of changes : None.  
Date of issue : 11/13/2014  
Other information : None.

*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*

31-SDS-SL-RUGLOCK  
DATE: 11-14-14  
REV: Release