

Statement of Performance

July 22, 2013

Product Description

- **Formula:** Spray-Lock® Wall Panel Adhesive
- **Flooring Material:** InPro/PVC
- **Material Acclimatization:** 48 Hours at 72 °F or 22 °C
- **Substrate Used:** Finished Drywall

General Adhesive Information

- See Technical Data for adhesive specifications

Performance

The test results produced a strong bond with acceptable peel and shear strength. Materials tested are approved for use with our adhesive over acceptable substrates. Spray-Lock® does not warrant the dimensional stability of the wall covering material regardless of its thickness.

Application Notes

Adhesive was applied as per standard instructions

Image of Material



Approved by

Michael Land
Director of R&D & Tech Services

This report applies to the specific product as supplied to Interlock for testing at the time of the test. Interlock is not responsible for bond performance changes due to conditions beyond our control such as manufacturing changes, composition changes, profile or finish changes, storage, or application techniques. Internal Quality Control methods were followed unless otherwise noted. This document does not represent the opinion of the material manufacturer. This document does not represent a guarantee or promise of performance of the products listed. It only describes testing performed under Interlock's conditions. No warranty is implied. This report shall not be reproduced except in full and with permission from Interlock. Interlock retains sole ownership of the data. Spray-Lock® does not warrant the dimensional stability of the wall panel material regardless of its thickness. Spray-Lock® should always be used in accordance with Interlock's issued instructions and procedures consistent with Country specific Standards for wall preparations and installation.