



# 3500

## Approved Sheet Goods

### SPRAY ADHESIVE



### PRODUCT CHARACTERISTICS

**Spray-Lock 3500** is a versatile spray adhesive naturally suited for adhering approved resilient sheet vinyl in commercial and residential application.

**Spray-Lock 3500** uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. 3500's shear strength is immediate after installation. Because of these unique characteristics, all traffic is allowed immediately. Adhesive indentation or displacement associated with heavy rolling loads is avoided.

**Spray-Lock 3500** allows for immediate heat welding after installation and total substitution of epoxies high in VOC content.

### ADVANTAGES

- Uses 80% less adhesive
- Heat weld immediately after installation
- Allows all traffic immediately (including hospital beds)
- 0.0 g/ml VOC content
- Water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

### SUITABLE SUBSTRATES

**Spray-Lock 3500** bonds approved resilient sheet vinyl to the following properly prepared, smooth, flat substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

### TECHNICAL CHARACTERISTICS

**Spray-Lock 3500** provides immediate shear strength after installation, allowing instant access to finished floor.

**Spray-Lock 3500** is solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

**Spray-Lock 3500** uses non-ozone depleting HFC propellant.

**Spray-Lock 3500** is warrantied up to 98% RH, 8 lbs MVER, and 11 pH.

\*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



[www.spraylock.com](http://www.spraylock.com)  
423.305.6151

# TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	3 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.0 g/ml per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 98% RH, 8 lbs/1,000 ft <sup>2</sup> /24 hr, and 11pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



## COVERAGE GUIDE

**SHEET GOODS | UPSIDE DOWN AEROSOL**  
**150-185 ft<sup>2</sup> (14-17.2 m<sup>2</sup>)**

**Note:** For Sheet Vinyl applications only, seams and perimeter require double coverage. In healthcare applications apply double coverage underneath bed footprint.