



6500 PLATINUM

Approved LVT and LVP

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock 6500 Platinum is a versatile spray adhesive naturally suited for adhering approved Luxury Vinyl Tile and Luxury Vinyl Plank in commercial and residential applications.

Spray-Lock 6500 Platinum uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. 6500 Platinum's instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

Spray-Lock 6500 Platinum is a 0.0 g/ml VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.0 g/ml VOC content
- Water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock 6500 Platinum bonds approved Luxury Vinyl Tile and Luxury Vinyl Plank to the following properly prepared, smooth, flat, dust-free substrates:

- Concrete

TECHNICAL CHARACTERISTICS

Spray-Lock 6500 Platinum provides immediate shear strength after installation, allowing instant access to finished floor.

Spray-Lock 6500 Platinum is solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock 6500 Platinum uses non-ozone depleting HFC propellant.

Spray-Lock 6500 Platinum is warrantied up to 99% RH, 10 lbs MVER, and 12 pH.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



www.spraylock.com
423.305.6151

TECHNICAL DATA

| | |
|------------------------------|--|
| CHEMICAL TYPE | Water-based acrylic blend |
| APPEARANCE | Milky white frost bubbles |
| ODOR | Sweet mild odor |
| FLASH POINT | Will not burn |
| NFPA 704 FLAMMABILITY RATING | 0 (Non-flammable) |
| SHELF LIFE | 3 years, if unopened |
| OPEN TIME | 4 hours |
| DRY TIME | Once adhesive is dry to touch (10-20 minutes) |
| VOC CONTENT | 0.0 g/ml per EPA Test Method 8260B |
| FOOT TRAFFIC ALLOWANCE | Immediately |
| HEAVY MACHINERY ALLOWANCE | Immediately |
| RESISTANCE TO MOISTURE | Excellent: 99% RH, 10 lbs/1,000 ft ² /24 hr, and 12pH |
| UNDERFLOOR HEATING SYSTEMS | Yes |
| STORAGE | Do not subject to freezing temperatures |



COVERAGE GUIDE

LVT, LVP | UPSIDE DOWN AEROSOL
100-125 ft² (9.3-11.6 m²)