



6500

For Approved LVT, LVP, Carpet Tile & Pad
SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock® 6500 is a versatile spray adhesive naturally suited for adhering approved Luxury Vinyl Tile, Luxury Vinyl Plank, Carpet Tile & Pad in commercial and residential applications.

Spray-Lock® 6500 uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. 6500's instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

Spray-Lock® 6500 is a 0.0 g/ml VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.0 g/ml VOC content
- Water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® 6500 bonds approved LVT, LVP, Carpet Tile & Pad to the following properly prepared, smooth, flat, and dust-free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

TECHNICAL CHARACTERISTICS

Spray-Lock® 6500 provides immediate shear strength after installation allowing instant access to finished floor.

Spray-Lock® 6500 is solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock® 6500 uses non-ozone depleting HFC propellant.

Spray-Lock® 6500 is warranted up to 95% RH, 8 lb MVER, and 11 pH.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

**Green Seal Certified: This product meets Green Seal™ Standard GS-36 based on effective performance and protective limits on VOCs and human and environmental toxicity. GreenSeal.org

TECHNICAL DATA

| | |
|------------------------------|---|
| CHEMICAL TYPE | Water-based acrylic blend |
| APPEARANCE | Milky white frost bubbles |
| ODOR | Sweet mild odor |
| FLASH POINT | Will not burn |
| NFPA 704 FLAMMABILITY RATING | 0 (Non-flammable) |
| SHELF LIFE | 3 years, if unopened |
| OPEN TIME | 4 hours |
| DRY TIME | Once adhesive is dry to touch (10-20 minutes) |
| VOC CONTENT | 0.0 g/ml calculated per EPA Test Method 8260B |
| FOOT TRAFFIC ALLOWANCE | Immediately |
| HEAVY MACHINERY ALLOWANCE | Immediately |
| RESISTANCE TO MOISTURE | Excellent: 95% RH, 8 lb/1,000 ft ² /24 hr, and 11 pH |
| UNDERFLOOR HEATING SYSTEMS | Yes |
| STORAGE | Do not subject to freezing temperatures |



COVERAGE GUIDE

LVT, LVP, CARPET TILE & PAD | UPSIDE DOWN AEROSOL

150-185 ft² (14-17.2 m²)