



FRP

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock® FRP Spray Adhesive bonds approved wall material for commercial and residential applications. Material must be structurally sound for use in commercial or residential applications.

Spray-Lock® FRP Spray Adhesive uses 60% less adhesive than traditional trowel-on adhesives.

Spray-Lock® FRP Spray Adhesive increases productivity with a faster application rate, saving time and money. Spray-Lock® FRP Spray Adhesive comes in an easy-to-use aerosol can.

ADVANTAGES

- Cuts labor cost by about 30%
- 4 hour working time
- Apply directly to wall/instant grab
- Releasable for repositioning (prior to rolling)
- Adheres to porous and non-porous substrates
- 0.0 g/ml VOC content
- Non-toxic, water-based adhesive
- Easy water cleanup while adhesive is still wet
- Non-flammable
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® FRP Spray Adhesive adheres approved wall coverings onto the following properly prepared smooth substrates:

- Plywood
- Drywall
- Water Resistant Drywall
- DensShield
- Metal
- FRP
- Ceramic Tile

NOTE: Prime all joint compound.

TECHNICAL CHARACTERISTICS

Spray-Lock® FRP Spray Adhesive formula is a water-based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock® FRP Spray Adhesive is solvent free, emits no harmful fumes, and contains 0.0 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock® FRP Spray Adhesive uses non-ozone depleting HFC propellant.

*Green Seal Certified: This product meets Green Seal™ Standard GS-36 based on effective performance and protective limits on VOCs and human and environmental toxicity. GreenSeal.org

**According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

TECHNICAL DATA

| | |
|------------------------------|--|
| CHEMICAL TYPE | Water-based acrylic blend |
| APPEARANCE | Milky white frost bubbles |
| ODOR | Sweet mild odor |
| FLASH POINT | Will not burn |
| NFPA 704 FLAMMABILITY RATING | 0 (Non-flammable) |
| SHELF LIFE | 3 years, if unopened |
| OPEN TIME | 4 hours |
| DRY TIME | Once adhesive is dry to touch (10-20 minutes) |
| VOC CONTENT | 0.0 g/ml calculated per EPA Test Method 8260B |
| STORAGE | Do not subject to freezing temperatures |
| CLIMATE-CONTROL SETTINGS | Building owners should become aware of the wall product manufacturer's guidelines for climate-control settings (temperature and humidity). These conditions must be monitored and kept constant to ensure the overall performance and long-term success of the installation. |



COVERAGE GUIDE

FRP ADHESIVE | 22 oz AEROSOL CAN

70 sq ft (6.5 m²)
2 sheets (8ft x 4ft)

Shake aerosol can well. Snap black tab on top of trigger to activate the can. Aim at desired substrate. Pull black lever to spray adhesive.

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented. Please refer to Installation Guidelines for detailed instructions.