



WALL TILE

SPRAY ADHESIVE

For use with the following:

- Flat & waffle backed tiles, 6"x6" or smaller
- Mesh-mounted mosaic tiles up to 12"x12"
- Porcelain, ceramic, stone, & glass tiles



PRODUCT CHARACTERISTICS

Spray-Lock Wall Tile Adhesive bonds approved wall tile for commercial and residential applications. Tiles must be structurally sound, clean, and flat (tiles should not rock back and forth when placed on a flat surface).

Spray-Lock Wall Tile Adhesive uses 60% less adhesive than traditional trowel applied adhesives.

Spray-Lock Wall Tile Adhesive increases productivity with a faster application rate, saving time and money. Spray-Lock Wall Tile Adhesive comes in an easy-to-use aerosol can.

ADVANTAGES

- Grout immediately
- No sagging / no shims or spacers
- Less mess and clean-up
- 1 hour open time
- No thinset or mastic in grout lines
- Faster installation
- Visible layout
- No mixing or troweling
- 0.0 g/mL VOC content
- Easy water cleanup while adhesive is still wet
- Non-flammable

SUITABLE SUBSTRATES

Spray-Lock Wall Tile Adhesive adheres approved wall tile onto the following properly prepared, smooth substrates:

- Water Resistant Drywall
- Hardie Board
- Green Board
- DensShield
- Plywood, Metal, Fiberglass, Glass, Primed/painted drywall
- Existing Wall Tile

NOTE: Joint compound must be primed.

TECHNICAL CHARACTERISTICS

Spray-Lock Wall Tile Adhesive formula is a water-based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock Wall Tile Adhesive is solvent free, emits no harmful fumes, and contains 0.0 g/mL VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock Wall Tile Adhesive uses non-ozone depleting HFC propellant.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	1 hour
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.0 g/mL calculated per EPA Test Method 8260B
STORAGE	Do not subject to freezing temperatures



COVERAGE GUIDE

WALL TILE | 16 oz AEROSOL CAN
40 ft² (3.7 m²)

Surfaces must be DUST FREE before adhesive is applied and kept DUST FREE while adhesive is drying before application of the wall tile.

Shake aerosol can well. Snap off tab on top of trigger to activate the can. Aim at desired substrate. Pull lever to spray adhesive.

Adjust spray pattern by applying less pressure to trigger for more control when closer to wall, more pressure to trigger for faster spray.

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented. Please refer to Install Guide for detailed instructions.