



FRP Adhesive

Spray-Lock FRP Adhesive is changing the rules when installing fiberglass reinforced panels (FRP), on both porous and non-porous substrates. With Spray-Lock FRP, a large area can be sprayed with a 4-hour working time. Constantly applying adhesive to the back of the panels and walls to compensate for shorter working times is no longer an issue. FRP also has instant grab that eliminates panels from sagging, and its low odor makes it ideal for installations in occupied spaces. (SKU: IL-FRP-22)

Coverage per single 22 oz can: 70 ft² (2 sheets - 8'x4')
Coverage per case of six cans: 420 ft²



Wall Tile Adhesive

Spray-Lock Wall Tile Adhesive (WTA) is an innovative application that cuts install time by over 50%. There are no sagging tiles nor any need for ledger board when working around a design, and tile can be installed over porous or non-porous substrates. Since grouting can begin within 1 hour of application, installers gain the flexibility to finish a backsplash or wall tile installation in only 1 day. Plus, Spray-Lock WTA's low profile makes it ideal for glass and stone mosaics. (SKU: IL-WTA-22)

Coverage per single 22 oz can: 40 - 50 ft²
Coverage per case of six cans: 240 - 300 ft²



RugLock

RugLock is a permanent spray-on non-slip rug backing that secures rugs to interior surfaces including hardwood, hard tiles, vinyl flooring and carpet. According to the National Safety Council, falls are the leading type of unintentional home-related injury deaths. With the introduction of RugLock, Spray-Lock has entered the consumer market with a real-world solution to a common household problem. (SKU: IL-RUGLOCK-16 & IL-RUGLOCK-10)

Coverage per single 16 oz can: 25 - 50 ft²
Coverage per case of six cans: 150 - 300 ft²
Coverage per single 10 oz can: 15 - 30 ft²
Coverage per case of six cans: 90 - 180 ft²



CERTIFICATIONS



Products bearing the FloorScore logo meet the indoor air quality emissions criteria of LEED, CHPS, the Green Guide for Healthcare, and are recognized by a long list of healthy building programs.



Products bearing the Green Seal Certified logo meet Green Seal™ Standard GS-36 based on effective performance and protective limits on VOCs and human and environmental toxicity.



Products bearing the CRI Green Label Plus logo are tested and found to have very low emissions of Volatile Organic Compounds (VOCs), setting a higher standard for indoor air quality (IAQ).



All Spray-Lock products exceed US EPA Indoor Air Quality Standards for VOCs, by having 0.0 g/mL VOCs, according to EPA Test Method 8260B.



5959 Shallowford Rd. Suite 405
Chattanooga, TN 37421
P: 423.305.6151 | F: 423.305.6150

WWW.SPRAYLOCK.COM

SKU: 32-SLBROCHURE Date: 11.07.16 REV: A



PRODUCTS

THE CONSTRUCTION INDUSTRY'S NEW STANDARD

PRODUCT SPECIFICATIONS

FULL LINE PREMIUM ECO ADHESIVES

Spray-Lock, Inc. has invented and produced a revolutionary line of Premium Eco Adhesives, using the world's most advanced and earth-friendly adhesive technology for floor and wall applications. Our products positively impact the environment by using up to 80% less adhesive while performing better than most trowel adhesives. Spray-Lock's flooring adhesives have low VOCs and high shear strength upon application, allowing immediate access to all traffic, even heavy weight-bearing loads. Plus, Spray-Lock Adhesives have the highest moisture and pH resistance in the industry. **To find out which formula is best for your flooring and substrate, visit www.spraylock.com for a list of flooring materials and the approved products for them.**



3100 & 3500 | Sheet Goods Adhesives

Spray-Lock 3100 and 3500 Sheet Vinyl Flooring Adhesives are ideal for time-sensitive sheet vinyl installations. They allow for heat welding and immediate access to flooring after installation is complete. Visit our website to find out which product will work best for your flooring and substrate. (SKU: IL-3100-22-UD & IL-3500-22-UD)

8 lbs. MVER, 95% RH, 11pH

Coverage per single 22 oz can: 150 - 185 ft²
Coverage per case of six cans: 900 - 1,110 ft²



6100 | Carpet Pad Adhesive

Spray-Lock 6100 is an incredibly efficient method for installing carpet pad. Weighing just 22 ounces, 6100 replaces the heavy trowel and bucket, increasing productivity. Like all Spray-Lock Adhesives, 6100 is ideal for installation in occupied spaces as it eliminates the need to shut down the HVAC or use fans to exhaust fumes from the building. (SKU: IL-6100-22-UD)

8 lbs. MVER, 95% RH, 11pH

Coverage per single 22 oz can: 150 - 185 ft²
Coverage per case of six cans: 900 - 1,110 ft²



6200 | Carpet Tile Adhesive

Spray-Lock 6200 is a revolutionary flooring adhesive designed for approved carpet tiles. It greatly reduces install time, and its releasability makes carpet tile replacement a fast repair job. Because there is no adhesive contamination on the reclaimed flooring, Spray-Lock 6200 is one of the only adhesives that allows for recycling of old discarded flooring. (SKU: IL-6200-22-UD)

8 lbs. MVER, 95% RH, 11pH

Coverage per single 22 oz can: 150 - 185 ft²
Coverage per case of six cans: 900 - 1,110 ft²



6500 | LVT Flooring Adhesive

Spray-Lock 6500 is designed for luxury vinyl planks and tiles (LVT). It has been installed and warranted for hundreds of millions of square feet. Spray-Lock 6500 greatly reduces install time, not only by expediting the application process but also by allowing the space to be opened to customers and other trade traffic immediately after the flooring installation. (SKU: IL-6500-22-UD)

8 lbs. MVER, 95% RH, 11pH

Coverage per single 22 oz can: 150 - 185 ft²
Coverage per case of six cans: 900 - 1,110 ft²



9500 | VCT Flooring Adhesive

Spray-Lock 9500 takes productivity to a new level for vinyl composite tile (VCT). It is at least 30% faster in adhesive applications when compared to trowel adhesives. Spray-Lock 9500's short tack time and longer working time speed up installation, eliminating the costly process of waiting for adhesive to set up. As soon as installation is complete, floors can be waxed, finished and opened to all traffic. (SKU: IL-9500-22-UD)

8 lbs. MVER, 95% RH, 11pH

Coverage per single 22 oz can: 170 - 200 ft²
Coverage per case of six cans: 1,020 - 1,200 ft²



6500 Platinum | LVT Flooring Adhesive

Spray-Lock 6500 Platinum has been leading the industry as a high moisture and pH tolerant adhesive for over 10 years. It has taken one national account's moisture failure rate of 23% down to less than 1% over a span of 300 million square feet. Whatever the cause for excessive moisture in subfloors, 6500 Platinum is a time-saving and reliable solution for fast track installation. (SKU: IL-6500P-22-UD)

10 lbs. MVER, 98% RH, 12pH

Coverage per single 22 oz can: 125 ft²
Coverage per case of six cans: 600 - 750 ft²



9500 Platinum | VCT Flooring Adhesive

Spray-Lock 9500 Platinum Adhesive is our warranted solution for installing VCT in high moisture environments. Unlike bucket adhesives that are loaded with low moisture tolerant fillers, 9500 Platinum is formulated with only pure polymers. In addition to having Spray-Lock's reliably short tack time and long working time, 9500 Platinum is the safeguard against failed VCT installations due to high moisture issues. (SKU: IL-9500P-22-UD)

10 lbs. MVER, 98% RH, 12pH

Coverage per single 22 oz can: 170 - 190 ft²
Coverage per case of six cans: 1,020 - 1,200 ft²



ESD 1005 | Conductive Spray Adhesive

Engineered to enhance the floor's ability to bring static charges safely to ground, Spray-Lock ESD Adhesive provides major time savings compared to traditional ESD adhesive applications. In fact, it is so advanced it provides a safe path to ground while using 80% less adhesive and offering superior protection against sub-floor moisture and pH. Spray-Lock ESD Adhesive is recommended for Electronic Manufacturing, Healthcare, Mission Control, IT Equipment and Computer Server Rooms. (SKU: IL-ESD-1005-22-UD)

7 lbs. MVER, 85% RH, 11pH

Coverage per single 22 oz can: 100 ft²
Coverage per case of six cans: 600 ft²

