



9500

Approved VCT Flooring

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock® 9500 is a versatile spray adhesive naturally suited for adhering Vinyl Composition Tile (VCT) in commercial and residential applications.

Spray-Lock® 9500 uses 80% less adhesive compared to trowel applied epoxy and bucket adhesive. 9500's instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

Spray-Lock® 9500 is a non-toxic, 0.020 g/ml VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.020 g/ml VOC content
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

SUITABLE SUBSTRATES

Spray-Lock® 9500 bonds approved VCT flooring to the following properly prepared, smooth, flat substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

DO NOT USE FORMULA 6500 FOR VINYL COMPOSITION TILE.

TECHNICAL CHARACTERISTICS

Spray-Lock® 9500 provides immediate shear strength after installation.

Spray-Lock® 9500 is solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock® 9500 uses non-ozone depleting HFC propellant.

Spray-Lock® 9500 withstands 8 lbs. of vapor emissions, 95% RH and 11 pH.

*Green Seal Certified: This product meets Green Seal™ Standard GS-36 based on effective performance and protective limits on VOCs and human and environmental toxicity. GreenSeal.org.

**According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



www.spraylock.com

423.305.6151

TECHNICAL DATA

| | |
|------------------------------|-------------------------------------------------|
| CHEMICAL TYPE | Water-based acrylic blend |
| APPEARANCE | Milky white frost bubbles |
| ODOR | Sweet mild odor |
| FLASH POINT | Will not burn |
| NFPA 704 FLAMMABILITY RATING | 0 (Non-flammable) |
| SHELF LIFE | 3 years, if unopened |
| OPEN TIME | 2 hours |
| DRY TIME | Once adhesive is dry to touch (10-20 minutes) |
| VOC CONTENT | 0.020 g/ml calculated per EPA Test Method 8260B |
| FOOT TRAFFIC ALLOWANCE | Immediately |
| HEAVY MACHINERY ALLOWANCE | Immediately |
| RESISTANCE TO MOISTURE | Excellent: 8 lbs/1,000 sq ft or 95% RH/11pH |
| UNDERFLOOR HEATING SYSTEMS | Yes |
| STORAGE | Do not subject to freezing temperatures |



COVERAGE GUIDE

VCT FLOORING | UPSIDE DOWN AEROSOL
170-200 sq ft