



Wall Tile

SPRAY ADHESIVE



PRODUCT CHARACTERISTICS

Spray-Lock® Wall Tile Adhesive bonds approved wall tile for commercial and residential applications. Tiles must be structurally sound with non-grooved backing for use in commercial or residential applications.

Spray-Lock® Wall Tile Adhesive uses 60% less adhesive than traditional trowel applied adhesives.

Spray-Lock® Wall Tile Adhesive increases productivity with a faster application rate, saving time and money. Spray-Lock® Wall Tile Adhesive comes in easy-to-use aerosol.

ADVANTAGES

- Grout after 1 hour
- No sagging / no shims or spacers
- Less mess and clean-up
- 1 hour open time
- No thinset or mastic in grout lines
- Faster installation
- Visible layout
- No mixing / No trowel
- 0.020 g/ml VOC content
- Easy water cleanup while adhesive is still wet
- Non-flammable

SUITABLE SUBSTRATES

Spray-Lock® Wall Tile Adhesive adheres approved wall tile onto the following properly prepared, smooth substrates:

- Water Resistant Drywall
- Hardie Board
- Green Board
- DensShield
- Plywood, Metal, Fiberglass, Glass, Primed Sheet Rock
- Existing Wall Tile

NOTE: Joint compound may need to be primed.

TECHNICAL CHARACTERISTICS

Spray-Lock® Wall Tile Adhesive formula is a water-based acrylic blend spray adhesive that has milky white frost bubbles in appearance and provides immediate shear strength during installation.

Spray-Lock® Wall Tile Adhesive is solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.

Spray-Lock® Wall Tile Adhesive uses non-ozone depleting HFC propellant.

*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.



www.spraylock.com

423.305.6151

TECHNICAL DATA

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	1 hour
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
STORAGE	Do not subject to freezing temperatures



COVERAGE GUIDE

WALL TILE | 22 oz AEROSOL CAN
40-50 sq ft (3.7-4.6 m²)

Surfaces must be **DUST FREE** before adhesive is applied and kept **DUST FREE** while adhesive is drying before application of the wall tile.

Please refer to the Wall Preparation Guide for detailed instruction on substrate conditioning before installation.

Shake aerosol can well. Snap blue tab on top of trigger to activate the can, aim at desired substrate. Pull blue lever to spray adhesive.

Coverage rates are a guide and figures will increase or decrease depending on the spraying technique implemented. Please refer to Installation Guidelines for detailed instructions.