



What Makes Spray-Lock's Flooring Warranties Unique?

*Spray-Lock's excellent five-year warranties just got better,
but what does that mean?*



- Applies to 3100, 3500, 6100, 6200, 6500, and 9500
- Covers materials and labor when used with one of over 600 approved flooring products (approved products list available on www.spraylock.com)
- Withstands substrate moisture levels up to 11 pH, 8 lbs. MVER, and 95% RH



- Applies to 6500 Platinum and 9500 Platinum
- Covers materials and labor when used with one of over 600 approved flooring products (approved products list available on www.spraylock.com)
- Withstands substrate moisture levels up to 12 pH, 10 lbs. MVER, and 98% RH



- Same coverage as 5-year warranties
- Approved and written on a job-specific basis only

NEW RH TOLERANCES

After thousands of installs over nearly 20 years, Spray-Lock's technical team continued to see the flooring adhesives outperform current warranty coverage. With this historical data in mind, the team then performed in-house testing over high RH slabs. After determining our adhesives could withstand higher moisture substrates, Technical decided to increase the Standard and Platinum tolerances to give better value and performance to our customers.

OUR PLATINUM LINE

For environments with uniquely high moisture substrates, we recommend our Platinum line for LVT and VCT installs. Both Platinum adhesives are specially formulated to withstand higher moisture vapor and pH levels. For an extended warranty, our Platinum Elite program provides additional coverage.

Got Questions?

More information about Spray-Lock's updated warranty coverage is available at www.spraylock.com.

For ordering and other questions, please contact your Regional Sales Manager or our Technical team at (423) 305-6151.